



PA700

Enterprise Digital Assistant

Unitech PA700 brings a new level of compact size, functionality and durable construction to an enterprise digital assistant. Not only delivering a slim device with stylish look, but also equipped with industrial-grade functions to meet the needs in mobile workforce. PA700 is an ideal portable tool to streamline work process in retail and field service.

Compact and elegant design

Unitech compact PA700 refined elegance to AIDC technology, with a slim form factor at weight of less than 285g (with battery) and stylish smooth round edges, PA700 is portable and easy to take around anywhere you go. In addition, a large 4.7-inch color TFT multi-touch display is a delight to watch and easy to operate by the two-finger gestures, it is available to be viewed even in direct sunlight, as well as a Gorilla® Glass screen with 7H hardness to keep it scratch free.

Versatile functionality

Packing a TI 1.5Ghz Dual Core Processor, DDR2 1GB SDRAM for system memory and 8GB NAND Flash for storage, PA700 also supports microSD expansion with an additional 32GB of storage capacity for data-intensive applications. Running on Android 4.1.1 Jelly Bean operation system, PA700 provides superior fast and smooth operation as well as combining 1D barcode scanning, NFC/HF RFID and 5.0MP auto focus camera in one handheld device, delivering maximum efficiency to users.

Advanced wireless connectivity

Equipped with advanced Bluetooth v4.0, GPS, Wi-Fi and wireless LAN 802.11 b/g/n tri-mode radios, PA700 enables wireless connections to other devices including servers, mobile computers and printers for the real-time data collections. Enterprise users can easily access information and accelerate their workflow while they're on the go. Besides, featuring latest NFC communication, PA700 provides convenient short-range communication between electronic devices. It enhances the service levels in task transferring and identity asset management applications.

Quality and durability

Engineered with superior materials, PA700 is built with the compliant with the MIL-STD-810F standards and IP65 certification, the rugged enterprise assistant survives through the harsh environments with its waterproof and dustproof ability and it can operate in temperatures from -10°C to 50°C. Unitech PA700 perfectly reflects its high reliability at a best.

Features

- Android 4.1.1 Jelly Bean operation system.
- Advanced performance with industrial grade 1.5Ghz Dual Core Processor
- Latest Bluetooth v4.0, GPS, Wi-Fi and wireless LAN 802.11 b/g/n tri-mode radios
- Large 4.7-inch color TFT multi-touch display
- Gorilla® Glass screen with 7H hardness to keep it scratch free.
- Rugged Construction: IP65 rated and 1.2M drop certified
- Built in 1D scanner and HF/NFC RFID Reader



System Features

| | |
|-------------------|--|
| CPU | TI OMAP 4470 1.5Ghz Dual Core Processor |
| Memory | 1GB Mobile DDR RAM 8GB eMMC Flash |
| OS | Android 4.1.1 Jelly Bean |
| Languages support | English, Simp. Chinese, Traditional Chinese, Japanese, Spanish, German, French |

Display

Gorilla Glass II with 5-point capacitive touch panel
4.7" Color 450nits High Brightness Transmissive TFT 720x1280 dots IPS LCD

Keypad

4 function keys, 2 scan keys, volume keys, power keys

Indicator

1 LED indicate charge/Message
Vibrator

Symbologies

1D CCD Barcode scanner

1D UPC-A/E, EAN-8/13, Codabar, Code 39, Code 39 full ASCII, Code 93, Code 32, Interleaved & Std. 2 of 5, EAN 128, Code 11, Delta, MSI/Plessey, Code 128, Toshiba, RSS expanded, RSS Limited, RSS14.

2D Imager

1D All major codes
2D PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode, Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal Dutch Postal (KIX)

Audio

1W speaker 85 dB at 10cm , 3.5mm Audio Jack, Receiver, Microphone

Regulatory Approvals

CE, NCC, FCC, BSMI, VCCI, CCC, RoHS compliance



Headquarters

Taipei, Taiwan
<http://www.ute.com> e-mail: info@hq.ute.com

Unitech America

Los Angeles
<http://us.ute.com> e-mail: info@us.ute.com
<http://can.ute.com> info@can.ute.com
Mexico
<http://latin.ute.com> e-mail: info@latin.ute.com

Unitech Asia Pacific & Middle East

Taipei
<http://apac.ute.com> info@apac.ute.com / info@india.ute.com
<http://mideast.ute.com> info@mideast.ute.com

Communication

| | |
|------------------------|---|
| Camera and Flash Light | 5MP CMOS Sensor Camera with dual Auto focus LED flash light |
| External storage | Support MicroSD memory card up to 32GB |
| USB | USB 2.0 OTG |
| WLAN | IEEE 802.11 b/g/n |
| Bluetooth | Bluetooth 4.0 |
| WWAN | GSM/GPRS/EDGE 850/900/1800/1900 MHzUMTS 850/900/1700/1900/2100 MHz WCDMA modem, HSPA+, DL: 21Mbps/ UL: 5.76Mbps |
| GPS | Yes |
| Other Sensors | eCompass Light & Proximity sensor G-sensor |
| RFID/HF (Optional) | Frequency: 13.56MHz Tag Support: ISO15693, ISO14443A , ISO14443B Support NFC |

Power Source

Main Battery 11.91Wh 3.7V @3220mAh Li-Ion battery pack

Enclosure

Weight 285g (with battery)
Dimension 160mm x17.4mm x 80mm (without engine)

Environmental

Operating temperature 14°F to 122°F (-10°C to 50°C)
Storage temperature -4°F to 140°F (-20°C to 60°C)
Charging Temperature 32°F to 104°F (0°C to 40°C)
Relative Humidity 5% ~ 95% (non-condensing)
Drop test to Concrete 1.2 meter
Environmental Sealing IP65
Vibration and Shock test MIL-STD-810F, 514.4 process II

Software

Android 4.1.1 API level 16

Accessories

Single Slot USB Client Cradle with Single Slot Battery Charger
Handstrap
3220mAH standard Battery
MicroUSB Cable
Power adaptor with universal plugs

Unitech Europe

Tilburg / Netherlands
<http://eu.ute.com> e-mail: info@eu.ute.com

Unitech Japan

Tokyo
<http://jp.ute.com> e-mail: info@jp.ute.com

Unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen
<http://cn.ute.com> info@cn.ute.com
Taipei <http://tw.ute.com> info@tw.ute.com

